Date: 22/04/2024

PCA4MA 4 … 25 bar 1/4 NPT-F , 1/2 -14 NPT-F

Compact pressure switch, flameproof Enclosure Ex d

Item number: 48751284

Quantity: 1 pcs.

Order code: PCA4MA-BAFB-1ASZZZ1ZZ CZKW
F4-C5- - - - -

Overview:
PCA4MA 4 … 25 bar 1/4 NPT-F , 1/2 -14 NPT-F
Compact pressure switch, flameproof Enclosure Ex d PCA
switch enclosure: stainless steel 316L
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
4 … 25 bar, working range -1 … 25 bar, proof pressure 60 bar
Set point definition: Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Compact pressure switch, flameproof Enclosure Ex d
Model PCA
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: stainless steel 316L
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
1xSPDT, silver contact
4 … 25 bar, working range -1 … 25 bar, proof pressure 60 bar
Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCA4MA 4 … 25 bar
Approvals / Certificates

© 2024 - WIKA Instruments s.a.r.l.

Date: 22/04/2024

IECEx-ATEX Ex d

© 2024 - WIKA Instruments s.a.r.l.