Product data sheet
Characteristics

ZCMC37L5
pre-cabled connection ZCMC - 3 Poles - PvR - 5 m



Main

Range of product	OsiSense XC
Product or component type	Pre-cabled connection
Component name	ZCMC
Associated body	ZCMD37
Number of poles	3
Contacts type and composition	2 NC + 1 NO
Contact operation	Slow-break, break before make

Complementary

Product compatibility	XCMD37
Electrical connection	Cable
Cable length	5 m
Wire insulation material	PvR

Packing Units

Package 1 Weight	0.450 kg

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.