DATASHEET - M22S-DRL-W-X0

Illuminated pushbutton actuator, RMQ-Titan, Flush, maintained, White, inscribed 0, Bezel: black

Part no. **M22S-DRL-W-X0**
216962

Product name	Eaton Moeller® series M22 Illuminated pushbutton actuator
Part no.	M22S-DRL-W-X0
EAN	4015082169626
Product Length/Depth	30 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.012 kilogram
Certifications	CSA Class No.: 3211-03 CE CSA File No.: 012528 UL UL File No.: E29184 IEC/EN 60947-5 UL 508 CSA UL Category Control No.: NKCR CSA-C22.2 No. 94-91 IEC/EN 60947 CSA-C22.2 No. 14-05 VDE 0660 DNV LR GL
Product Tradename	M22
Product Type	Illuminated pushbutton actuator
Product Sub Type	None
Bezel color	Black
Bezel material	Plastic
Design	Flush Classical
Features	Labelled
Fitted with:	Front ring
Functions	Stay-put/spring-return function can be changed on device
Inscription	Inscribed
Degree of protection	IP66 NEMA 3R NEMA 12 NEMA 13 IP67 NEMA 4X IP69K
Degree of protection (front side)	NEMA 4X IP67/IP69K
Lifespan, mechanical	1,000,000 Operations (AC operated)
Opening diameter	22.5 mm
Operating frequency	1800 Operations/h
Product category	RMQ-Titan
Size	Front diameter: 29.7 mm
Suitable for	Illumination
Type	Illuminated pushbutton actuator
Mounting position	As required
Shock resistance	30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27

Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Connection to SmartWire-DT		With SWD-RMQ connections Yes
Actuating force		5 N
Actuator color		White
Actuator function		Switching function latching Maintained
Force for positive opening - min		0 N
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014])

Colour button		White
Number of command positions		1
Construction type lens		Round
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
Type of button		Flat
Suitable for illumination		Yes
With protective cover		No

Labelled	Yes
Switching function latching	Yes
Spring-return	No
With front ring	Yes
Material front ring	Plastic
Colour front ring	Black
Degree of protection (IP), front side	IP67/IP69K
Degree of protection (NEMA), front side	4X

© 04/2023 by Eaton Industries GmbH