Date: 10/04/2023

S-11 ; 0 ... 20 bar; 0 ... 20 mA, 3-wire

Pressure transmitter for general applications

Item number:	14029379	
Quantity:	1 pcs.	
Order code:	S-11-B-BEL-86-Q1ZGA4ZAZ-ZZZ	W101Z-ZZ-F3ASZZ-ZFOSE3
Overview:	S-11 ; 0 ... 20 bar; 0 ... 20 mA, 3-wire @ 10 ... 30 V DC; Accuracy: 0.5% of span G 1/2 B, flush diaphragm with O-ring Wetted parts: stainless steel Sealing: NBR; 4-pin L-plug DIN EN 175301-803, IP65 UB=1, 0V=2, S+=3 Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F) Specifications according to data sheet: PE 81.02	
Details:	Pressure transmitter for general applications Model S-11 with flush diaphragm Specifications according to data sheet: PE 81.02 Power supply: DC 10 (14) ... 30 V Case: stainless steel Output signal: 0 ... 20 mA, 3-wire Measuring range: 0 ... 20 bar Process connection: G 1/2 B, flush diaphragm with O-ring Wetted parts: stainless steel Sealing: NBR Accuracy: 0.5% of span Electrical connection: 4-pin L-plug DIN EN 175301-803, IP65 Permissible medium temperature: -30 ... +100 °C (-22 ... +212 °F) Power supply: 10 ... 30 V DC Pin assignment: UB=1, 0V=2, S+=3 shield: standard WIKA standard - specification according to data sheet Test protocol: without test protocol Certificates: without Import documentation CIS-States: without	

© 2023 - WIKA Instruments s.a.r.l.