## CAT. N° 0 566 21



# COMBINED UNIT P17 - WITHOUT RAIL 125X220 - IP55 - 200/250 V~ - 16 A - 2P+E

| | |
|---|---|
| Pack (number of units) | 1 |
| Volume (dm³) | 5 |
| Weight (g) | 975,00 |

## Product characteristics

**16 and 32 A sockets - 200 to 250 V~ - 50/60 Hz**

- IK 08 according to IEC 62262
- Conform to IEC 60439-1
- Supplied without cable glands
- Self-extinguishing: 650 °C

**2P+E - without rail**

- 125 x 220 mm
- 16 A - IP 55
- IP 55 according to IEC 60529 and EN 60529

## General characteristics

**P 17 Tempra combined units LV 16 to 63 A - interlocked switched sockets**

## Documentation

**Catalogue pages & additional information**

- Selection chart (p.389)

**Installation & technical data**

- F00140EN-05

**Installation instructions & related documents**

- 250046003

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.