Specifications

# Eaton C14M32

## Catalog Number: C14M32

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 32 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CH14 Modular fuse holder




### General specifications

**Product Name**
Eaton Bussmann series low voltage cylindrical fuse

**Catalog Number**
C14M32

**EAN**
5027590494878

**UPC**
051712754729

**Product Length/Depth**
51 mm

**Product Height**
14.3 mm

**Product Width**
14.3 mm

**Product Weight**
20.6 g

**Compliances**
CE Marked
GoST-R
RoHS Compliant

**Certifications**
IEC 60269

Powering Business Worldwide

## Electrical data

### Amperage Rating

32 A

### Voltage rating

500 V

### Voltage type

AC

### Breaking capacity

120 kA

### Utilization category

aM (switchgear protection)

### Frequency rating - max

62 Hz

## Compatible fuse holder

### Suitable for

CH14 Modular fuse holder

## Resources

### Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

### Declarations of conformity

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

### Technical data sheets

720115 Cylindrical fuses

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia