Specifications

Eaton 315NHG03BI

Catalog Number: 315NHG03BI

Fuse-link, LV, 315 A, AC 500 V, NH03, gL/gG, IEC, dual indicator, insulated gripping lugs

General specifications

Product Name
Eaton Bussmann series low voltage NH Fuse

Catalog Number
315NHG03BI

EAN
5027590476393

Product Length/Depth
150 mm

Product Height
70 mm

Product Width
53 mm

Product Weight
657 g

Compliances
CE Marked
RoHS Compliant

Certifications
IEC 60269-1
IEC 60269-2
DIN 43620

Product specifications

Type

Fuse

Application

industrial

Utilities, Solar, Wind

Amperage Rating

315 A

Fitted with:

Insulated metal gripping lugs

Fuse size

NH03

Current type

AC

Breaking capacity

120 kA

Rated switching capacity

120 kA

Rated voltage AC

500 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

Yes

Watt losses

21 W

Connection

Blade end

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

NH Fuse links, bases and gear

Declarations of conformity

CE NH Size 03, 500V fuse-links

UKCA NH Size 03, 500V fuse-links

Multimedia

Eaton Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

10164 NH 500 Volts gG

Technical service bulletins

Datasheet - 315NHG03BI

Construction

NH03

Construction size

NH03

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

500 V

Rated switching capacity AC

120 kA

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia