Date: 12/04/2023

MW-XXUN - 0...10 bar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F

Diaphragm pressure switch, Stainless steel case

Item number: 48781627

Quantity: 1 pcs.

Order code: MW-XXUN-BBJSC-2AMZZZZZZZZZZZZZZZZZZZZZZ ZCK2AW B000440IZZZZZZZZ

Overview:
MW-XXUN - 0...10 bar - Adaptor 1/2 NPT-M - 1/2 -14 NPT-F
Diaphragm pressure switch, Stainless steel case
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 1x SPDT silver contact
setting range: 0...10 bar
Standard, working range = 0...10 bar, proof pressure 20 bar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Stainless steel AISI 304/O-Ring: FPM/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point customer-specifically configured
1. set point: 4.40 bar increasing,

Details:
Diaphragm pressure switch, Stainless steel case
Model MW
Specifications according to data sheet: PV 31.10
Repeatability of set point: ≤ 1% of span
Contact version: 1x SPDT silver contact
setting range: 0...10 bar
working range: Standard, working range = 0...10 bar, proof pressure 20 bar
Set Point customer-specifically configured
Unit: bar
Process connection: Adaptor 1/2 NPT-M
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66
MW-XXUN
Diaphragm: Stainless steel AISI 304/O-Ring: FPM/Connection: Stainless steel AISI 316L

© 2023 - WIKA Instruments s.a.r.l.

1. set point: 4.40 bar increasing,

© 2023 - WIKA Instruments s.a.r.l.