

Versatile two and three arm mechanical pullers

SKF Standard Jaw Pullers TMMP series

One of the most common ways to dismount small to medium size bearings is to use a basic mechanical puller. Using an SKF puller helps to safeguard against damage to the bearing or to the bearing seating during dismounting. SKF Jaw pullers allow for easy and safe puller operation.

- Range of five different jaw pullers with two or three arms
- Maximum nominal span from 65 to 300 mm *(2.6 to 11.8 in.)*
- Cone system for automatic centring and secure positioning of arms
- Strong springs keep arms apart for easy operation
- Hardened, high quality carbon steel

Technical data

Designation	TMMP 2x65	TMMP 2x170	TMMP 3x185	TMMP 3x230	TMMP 3x300
No. of arms	2	2	3	3	3
Width of grip	15–65 mm *(0.6–2.6 in.)*	25–170 mm *(1.0–6.7 in.)*	40–185 mm *(1.6–7.3 in.)*	40–230 mm *(1.6–9.1 in.)*	45–300 mm *(1.8–11.8 in.)*
Effective length of arm	60 mm *(2.4 in.)*	135 mm *(5.3 in.)*	135 mm *(5.3 in.)*	210 mm *(8.3 in.)*	240 mm *(9.4 in.)*
Claw height	8 mm *(0.31 in.)*	9 mm *(0.35 in.)*	9 mm *(0.35 in.)*	9 mm *(0.35 in.)*	11 mm *(0.43 in.)*
Maximum withdrawal force	6,0 kN *(0.7 US ton)*	18,0 kN *(2 US ton)*	24,0 kN *(2.7 US ton)*	34,0 kN *(3.8 US ton)*	50,0 kN *(5.6 US ton)*
Weight	0,5 kg *(1.2 lb)*	2,1 kg *(4.7 lb)*	2,9 kg *(6.4 lb)*	5,8 kg *(13 lb)*	8,6 kg *(19 lb)*



® SKF is a registered trademark of the SKF Group.

© SKF Group 2014
The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 13069 EN · December 2014