Date: 25/04/2023

PG23HP-S.160...F 2500 bar G1/2B lower mount

"Bourdon Tube Pressure Gauge, Safety Pattern"

Item number:	48805544	
Quantity:	1 pcs.	
Order code:	PG23HP-S3-F-5H-F-BG625Z-GD-UZHQCZZ-ZZZ IZZZZZZ11ZZZ	313DDZIYW01-
Overview:	PG23HP-S.160...F 2500 bar G1/2B lower mount class 1.6 Ingress protection: IP 65 Case filling fluid: Silicon oil M50 Restrictor: stainless steel, D 0.6 with thread protection Pressure Gauge Standard: International (standard Europe) *WIKA* Serial number on label	
Details:	"Bourdon Tube Pressure Gauge, Safety Pattern" High Pressure starting at 2000 bar Model PG23HP-S Specifications according to data sheet: PM 02.28 Measuring system: stainless steel Liquid Damping (case filling): with Nominal size: 160 mm Measuring range: gauge pressure range Scale range: 0...2500 bar Process connection: G 1/2 B Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: standard pointer Accuracy class: class 1.6 Case filling fluid: Silicon oil M50 Ingress protection: IP 65 Permissible medium temperature: + 100 °C with thread protection Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* Serial number on label	

© 2023 - WIKA Instruments s.a.r.l.