PNOZ m EF EtherCAT FSOE 772123



Configurable safe small controllers PNOZmulti 2, fieldbus module, EtherCAT FSoE Master.

Technical details

General data	
Approval:	CE, UKCA, EAC (Eurasian), TÜV
Technical data	
Electrical data	
Purpose of U1:	Module supply
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	3 W
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	0 - 60 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-30, EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
EMC to standard ...:	EN 61131-2
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2

Protection type standard:	EN 60529
Mechanical data	
Mounting position:	horizontal on top hat rail
Housing material lower section:	PC
Connection terminal:	Spring-loaded terminal, Screw terminal
Height dimension:	101.4 mm
Width dimension:	22.5 mm
Depth dimension:	115 mm
Net weight:	115 g
Gross weight:	130 g
Environment	
WEEE classifikation (08/2018):	5 devices (feed size < 50cm)
Commercial data	
EAN-Code:	4046548097078
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27242208
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001423
Volume:	0 dm3