Date: 22/04/2024

F2808 1,000 N ±0.15% Fnom 2.0 ±0.2 mV/V tension/compression

Miniature Tension-/Compression force transducer S-Type

Item number:	83800543
Quantity:	1 pcs.
Order code:	SPP-F2808-M2310C3A4K010300XXXXXXXXXXXXXXXXXXXX M1166FO5168
Overview:	F2808 1,000 N ±0.15% Fnom 2.0 ±0.2 mV/V tension/compression Model: F2808 Tension/compression force transducer, S-Typ, female thread Force direction: tension/compression Rated force/Rated load: 1,000 N Relative linearity error: ±0.15% Fnom Output signal: 2.0 ±0.2 mV/V Electrical connection: Cable output, free wires Cable length: 3 m Force transmission: M8 Ingress Protection IP: IP66 Technical data acc. to datasheet: FO51.68
Details:	Miniature Tension-/Compression force transducer S-Type Model: F2808 Miniature S-Type up to 2,000 N Force direction: tension Unit: N Nominal load: 1000 N Output signal: 2 mV/V, 4-wire Electrical connection: cable outlet, length 3m Cable length in m: 3,0m Data sheet: FO 51.68 Product Name: Tension/compr. force transd. Mini. S-Typ SPP-Tension-/compression force transducer, model F2808 Technical data acc. to datasheet: FO51.68 Model: F2808 Tension-/compr. force transd., S-Type Miniature,female thread, 0..5N-0..2,000N Force direction: tension/compression Rated force/Rated load: 1,000 N Relative linearity error: ±0.15% Fnom Output signal: 2.0 ±0.2 mV/V Electrical connection: Cable output, free wires Cable length: 3 m Force transmission: M8 Ingress Protection IP: IP66 Miniature Tension-/Compression force transducer S-Type Model: F2808 Miniature S-Type up to 2,000 N Force direction: tension

© 2024 - WIKA Instruments s.a.r.l.

Unit: N
Nominal load: 1000 N
Output signal: 2 mV/V, 4-wire
Electrical connection: cable outlet, length 3m
Cable length in m: 3,0m
Data sheet: FO 51.68
Product Name: Tension/compr. force transd. Mini. S-Typ

© 2024 - WIKA Instruments s.a.r.l.