Specifications

Eaton 9PX5KIRTNG2

Eaton 9PX Gen2 UPS Netpack, 5000 VA, 5000 W, Input: Hardwired, Outputs: (6) C13, (6) C39, Hardwired, Rack/tower, 3U, Gigabit Network card included, Rack-mounting kit included

General specifications	
PRODUCT NAME	Eaton 9PX Gen2 UPS
CATALOG NUMBER	9PX5KIRTNG2
EAN	3553340710551
PRODUCT LENGTH/DEPTH	684 mm
PRODUCT HEIGHT	130 mm
PRODUCT WIDTH	440 mm
PRODUCT WEIGHT	43.1 kg
WARRANTY	3 year on electronics, 2 year on battery
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 ENERGY STAR certified CE cULus UKCA Cm Ukr RCM
MODEL CODE	Eaton 9PX 5000i RT3U Netpack G2

Powering Business Worldwide

Additional information

CONSTRUCTION TYPE	482.6 mm (19 inch) device
PACKAGE CONTENTS	• UPS • (2) cable glands • (2) IEC-IEC output cables (1,2m) • USB cable (1,8m) • Network Management Card • Supports for tower mounting • Rack-mounting kit with brackets and slides for UPS • Safety instructions • Quickstart guide
INTERNAL BYPASS	Yes
AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black/silver
EFFICIENCY AT MAX. LOAD	96.7
RACK MOUNTING KIT	Yes
HOT SWAP POWER	No

Battery

BATTERY TYPE	Sealed, lead-acid
RUNTIME GRAPH	View runtime graph
BATTERY QUANTITY	15
BATTERY MANAGEMENT	• ABM+ (Predictive battery life) & Temperature compensated charging method (user selectable) • Automatic battery test • Deep discharge protection • Automatic recognition of external battery units
BATTERY RATING	12 V / 5 Ah
EXTENDED BATTERY CAPABILITY	Yes

Communication

INCLUDES NETWORK CARD	Yes
COMMUNICATION	• USB port (HID compliant) • Serial port (RS232) • Mini terminal block for remote On/Off • Mini-terminal block for remote power off • Mini-terminal block for dry contacts outputs (2 contacts) • Network card
ETHERNET INTERFACE	Yes
USER INTERFACE	Multilingual graphical LCD display
POTENTIAL FREE SWITCH CONTACT	Yes
EXPANSION SLOTS	One slot, network card included
SOFTWARE COMPATIBILITY	Eaton Brlightlayer Software suite
TYPE OF INTERFACE	Other

Electrical input

NOMINAL FREQUENCY	50/60 Hz
INPUT POWER FACTOR	>.99
INPUT VOLTAGE RANGE	176-276 V (100-276 V with derating)
INPUT FREQUENCY RANGE	40-70 Hz

Electrical output

RECEPTACLE	(6) C13, (6) C39, Hardwired
VOLTAGE	230V
VA RATING	5000 VA
WATTAGE	5000W
OUTPUT POWER FACTOR	1
OUTPUT VOLTAGE RANGE	200/208/220/230/240 V +/- 1%
OUTPUT WAVEFORM	Sine wave
OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	1
FEED TYPE	1
TOPOLOGY	Online/Double-conversion

Environmental

ALTITUDE	3000 m
NOISE LEVEL	<40 dB at 1 meter
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
RELATIVE HUMIDITY	0-95% non-condensing

Resources	
BROCHURES	Eaton 9PX Gen2 EMEA Brochure - EN
COMPLIANCE INFORMATION	Eaton single phase UPS Transportation document according to DGR
DECLARATIONS OF CONFORMITY	Eaton 9PX Gen2 Declaration of Conformity
MANUALS AND USER GUIDES	Eaton 9PX Gen2 UPS Advanced user guide - EN
MULTIMEDIA	Eaton 9PX Gen2 Video
PEP ECO-PASSPORT	eaton-double-conversion-network-ups-pep-eato-00281-v0102-en.pdf

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.