reolink	Reolink Innovation Limited	G2K4GSBM64-UK
Picture		

Camera	**Video & Audio**	Image Sensor	1/3" CMOS Sensor
		Video Resolution	2560 x 1440 (4.0 megapixel) at 15 frames/sec
		Video Format	H.265
		Field of View	Fixed lens, horizontal: 95°; vertical: 52°; diagonal: 115°
		Infrared Night Vision	up to 10 meters (33ft) (LED: 6pcs/14mil/850nm)
		Digital Zoom	16x digital zoom
		Audio	Two-way audio
	PIR Detection & Alerts	Smart Alarm	PIR detection/person detection/vehicle detection
		PIR Detecting Distance	Adjustable up to 10m (33ft)
		PIR Detecting Angle	120° horizontal
		Audio Alert	Customizable verbal alerts
		Recording	Motion triggered recording
		Other Alerts	Instant email alerts and push notifications
	3G/4G	Frequency Bands	Europe Version: LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8
		Transmission Data	LTE FDD: Max. 10Mbps(DL), Max. 5Mbps(UL)
			LTE TDD: Max. 8.96Mbps(DL), Max. 3. 1Mbps(UL)
			HSPA+: Max. 42Mbps(DL), Max. 5.76Mbps(UL)
			UMTS: Max. 384Kbps(DL), Max. 384Kbps(UL)
	Power	Battery	7800mAh rechargeable battery (Battery life varies based on settings, usage & temperature.)
		Solar	Reolink Solar Panel
		DC Power	5V/2A USB power adapter
	Storage	Local Storage	Supports up to 128GB micro SD card (Included 64GB microSD Card)
		Cloud Storage	Supports Reolink Cloud (available in some countries)
	Smart Home	Smart Home	Works with Google Assistant
	Working Environment	Operating Temperature	- 10°C to 55°C (14°F to 131°F)
		Weather Resistance	IP65 weatherproof
	Size & Weight	Size	Φ75 x 194mm (2.95 x 7.63 in)
		Weight (Battery Included)	450g (15.9oz)
	Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.
Solar Panel	**Electrical Parameters**	Max Voltage	6.0V
		Max Current	530mA
		Max Power	3.2W
	Size & Weight	Dimensions	185.4x120.4x6.5(mm)
		Cable Length	4 meters (157.48in)
		Weight	280g (9.9oz)
		Interface	Micro USB Port
	Other Parameters	Working Temperature	- 10°C to 55°C (14°F to 131°F)
		Working Humidity	10%~90%
		Weather Resistance	IP65
	Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support .reolink.com/hc/en-us/