CA5-10

Print View..
Print to Pdf..

Search → OK
Products & Services only

+ Rate this page
+ Share this page

Your preferences:

United States of America → OK
English → OK

ABB contact for United States of America

Select another country → OK

General Information

Extended Product Type:	CA5-10
Product ID:	1SBN010010R1010
ABB Type Designation:	CA 5-10
EAN:	3471522121004
Catalog Description:	CA5-10 Auxiliary Contact Block
Long Description:	CA5-10 Auxiliary Contact Block



Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Block Contactors Accessories

Parts & Services » Robotics » After Sales Products » Parts Program » Other Robot Parts

Ordering

EAN:	3471522121004
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369085

Dimensions

Product Net Weight:	0.143 kg

Container Information

Package Level 1 Gross Weight:	0.143 kg
Package Level 1 EAN:	3471522121004

Do you need professional PDFs? Try PDFmyURL!

Environmental

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
IIT Publishing Status:	Level 0 - Information enabled
Maximum Electrical Switching Frequency:	1200 cycles per hour
Maximum Mechanical Switching Frequency:	3600 cycles per hour
Mechanical Durability:	A9 ... A75 10 million A95 ... A110 3 million
Minimum switching capacity [V/mA]:	A9 ... A75 17 / 5 volt per milliamp A95 ... A110 24 / 50 volt per milliamp
Mounting on Contactors:	A 9...A 75
Mounting Position:	Front face
Number of Auxiliary Contacts NO:	1
Power Loss:	Per Pole 0.1 W
Product Main Type:	Accessories for Block Contactors
Product Name:	Auxiliary Contact Block
Rated Breaking Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Insulation Voltage (U_i):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Making Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15
Rated Operational Current AC-15 (I_e):	(220 / 240V) 4 A (24 / 127V) 6 A (380 / 440V) 3 A (500V) 2 A (690V) 2 A
Rated Operational Current DC-13 (I_e):	(125V) 0.55 / 69 A (24V) 6 / 144 A (250V) 0.3 / 75 A (48V) 2.8 / 134 A (72V) 1 / 72 A

Do you need professional PDFs? Try **PDFmyURL!**

PDFmyURL

Rated Operational Voltage:	Auxiliary Circuit 690 V Main Circuit 24 V
Rated Short-time Withstand Current (I_{cw}):	for 1.0s 140.0 A
Remarks:	100
Technical Information:	AUXILIARY SWITCH BLOCK
Terminal Type:	Screw Terminals

Certificates and Declarations (Document Number)

CSA Certificate:	CSA_1033838
cUL Certificate:	UL_071301E48139
EAC Certificate:	EAC_RU C-FR ME77 B01048
GOST Certificate:	GOST_POCCFRME77B07175
RINA Certificate:	RINA_ELE128713XG001
UL Certificate:	UL_071301E48139

Classifications

E-nummer:	3228800
ETIM 4.0:	EC002498 - Accessories for low-voltage switch technology
ETIM 5.0:	EC002498 - Accessories for low-voltage switch technology
Object Classification Code:	K
UNSPSC:	39120000

Provider information/Impressum © Copyright 2014 ABB. | Cookies and privacy policy | Login

Facebook | Twitter

Do you need professional PDFs? Try **PDFmyURL!**

PDFmyURL