Date: 25/04/2023

PG23HP-S.100...D 2000 bar 9/16-18 UNF female, Autoclave Engineers F-250-C lower mount

"Bourdon Tube Pressure Gauge, Safety Pattern"

Item number:	48732614
Quantity:	1 pcs.
Order code:	PG23HP-S3-D-5H-E-BG620Z-VV-UZHZCZZ-ZZZ 313D1ZI3W01-IZZZZZZ11ZZZ
Overview:	PG23HP-S.100...D 2000 bar 9/16-18 UNF female, Autoclave Engineers F-250-C lower mount class 1.6 Ingress protection: IP 65 with thread protection Pressure Gauge Standard: International (standard Europe) *WIKA* Serial number on label
Details:	"Bourdon Tube Pressure Gauge, Safety Pattern" High Pressure starting at 2000 bar Model PG23HP-S Specifications according to data sheet: PM 02.28 Measuring system: stainless steel Liquid Damping (case filling): without filling Nominal size: 100 mm Measuring range: gauge pressure range Scale range: 0...2000 bar Process connection: 9/16-18 UNF female, Autoclave Engineers F-250-C Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Accuracy class: class 1.6 Case filling fluid: prepared for filling Ingress protection: IP 65 Permissible medium temperature: + 200 °C with thread protection Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* Serial number on label

© 2023 - WIKA Instruments s.a.r.l.