Date: 11/04/2023

F73.100/4, -80...+60°C, L1=325x6mm,

Gas actuated thermometer, stainless steel series

Item number:	48768134
Quantity:	1 pcs.
Order code:	F73.100-CHA-4ND-B0325-S02-4-Z-HZZ-AHAZZZ G7 FZZZEVZZIWS-AZ1ZZZZZ2ZZZZ
Overview:	F73.100/4, -80...+60°C, L1=325x6mm, 1/2 NPT radial bottom Surface mounting bracket, die cast aluminium stainless steel armoured capillary Capillary length: 2 m laminated safety glass Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.100, nominal size 100, with capillary Unit: °C Scale range: -80 °C ... +60 °C Connection design: 4, compression fitting, sliding on stem Process connection: 1/2 NPT Stem diameter: 6 mm Insertion length L1: 325 Capillary: stainless steel armoured capillary Capillary length: 2 m Design of case mounting: Surface mounting bracket, die cast aluminium Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: radial bottom Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.