Date: 11/04/2023

A5500/1, NS100, -30...+70°C, L1=276x8mm

Bimetal thermometer, stainless steel version

Item number:	48769625
Quantity:	1 pcs.
Order code:	A5500 -1-CCD-BK-C276HZZ-AHAZZZZ TB FZZZEPZSVID-AZ1ZZZZZ1ZZZZ
Overview:	A5500/1, NS100, -30...+70°C, L1=276x8mm Process connection: plain, without thread, axial laminated safety glass, class 1 per EN 13190 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) *WIKA* Serial number *...*
Details:	Bimetal thermometer, stainless steel version Specifications according to data sheet: TM 55.01 Case: stainless steel Stem material: stainless steel Model: A 5500, nominal size 100, location of stem centre back (axial) Connection design: 1, plain stem Unit: °C Scale range: -30 °C ... +70 °C Process connection: plain, without thread Stem diameter: 8 mm Insertion length L1: 276 mm Window: laminated safety glass Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Case: Stainless steel Connector location: axial Version: standard Stem material: stainless steel Permissible ambient temperature: -40 ... +70 °C Manufacturer logo: *WIKA* Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 serial number on dial: Serial number *...* Explosion protection: ATEX Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.