
TIMKEN

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number 33287 - 33462, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Basic Load Ratings | Factors

Specifications

Series	33000
Cone Part Number	33287
Cup Part Number	33462
Design Units	Imperial
Bearing Weight	2.60 lb 1.200 Kg
Cage Type	Stamped Steel

Dimensions

d - Bore	2.8750 in 73.025 mm
D - Cup Outer Diameter	4.6250 in 117.475 mm

B - Cone Width	1.1875 in 30.163 mm
C - Cup Width	0.9375 in 23.813 mm
T - Bearing Width	1.1875 in 30.163 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius[1]	0.14 in 3.560 mm
r - Cup Backface "To Clear" Radius[2]	0.130 in 3.30 mm
da - Cone Frontface Backing Diameter	3.87 in 81.03 mm
db - Cone Backface Backing Diameter	3.46 in 87.88 mm
Da - Cup Frontface Backing Diameter	4.45 in 113.00 mm
Db - Cup Backface Backing Diameter	4.09 in 103.89 mm
Ab - Cage-Cone Frontface Clearance	0.07 in 1.8 mm
Aa - Cage-Cone Backface Clearance	0.07 in 1.8 mm
a - Effective Center Location[3]	-0.11 in -2.80 mm


Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)[4]	8060 lbf 35900 N
C1 - Dynamic Radial Rating (1 million revolutions)[5]	31100 lbf 138000 N
C0 - Static Radial Rating	44300 lbf 197000 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)[6]	6020 lbf 26800 N

Factors

K - Factor[7]	1.34
e - ISO Factor[8]	0.44
Y - ISO Factor[9]	1.38
G1 - Heat Generation Factor (Roller-Raceway)	84.2
G2 - Heat Generation Factor (Rib-Roller End)	24.4
Cg - Geometry Factor	0.116

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These maximum fillet radii will be cleared by the bearing corners.
[3] Negative value indicates effective center inside cone backface.
[4] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.
[5] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.
[6] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.
[7] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[8] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[9] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e	0.44	
ISO Factor - Y	1.38	
Bearing Weight	2.6	lb
Number of Rollers Per Row	23	
Effective Center Location	-0.11	inch

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

33287 - 33462
TS BEARING ASSEMBLY

K Factor	1.34	
Dynamic Radial Rating - C90	8060	lbf
Dynamic Thrust Rating - Ca90	6020	lbf
Static Radial Rating - C0	44300	lbf
Dynamic Radial Rating - C1	31100	lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY