Specifications

Eaton 50D33R

Catalog Number: 50D33R

Eaton Bussmann series low voltage D fuse, Ultra-rapid, 500V, 50A, Non Indicating, fuse, Class gR, Ultra rapid, White, Ceramic body



General specifications

Product Name
Eaton Bussmann series low voltage D fuse

Catalog Number
50D33R

EAN
5027590482912

UPC
051712835626

Product Length/Depth
50 mm

Product Height
27 mm

Product Width
27 mm

Product Weight
52.16 g

Compliances
CE Marked
GoST-R
RoHS Compliant

Certifications
IEC 60269
VDE
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Powering Business Worldwide

Product specifications

Type

fuse

Special features

Ultra-rapid

Application

For domestic and general industrial applications

Amperage Rating

50 A

Fuse size

DIII

Breaking capacity

50 kA

Construction size (fuse inserts)

DIII

Rated voltage AC

500 V

Class

Class gR

Fuse type

D33R - Ultra rapid

Accessory/spare part type

50GD33 White screw cap gauge piece

Utilization category

gR (general purpose semiconductor protection)

Color

White

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Connection

Other

Construction

D3

Construction size

Resources

Brochures

eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf

Catalogs

CA134002EN

Declarations of conformity

CE Bottle fuse-links, holders, carriers and accessories

UKCA Bottle fuse-links, holders, carriers and accessories

DIII

Fuse shape

Bottle

Response time

Ultra rapid

Suitable for

E33/DIII Fuse base

TFD33 Fuse base screw fixing

SFRD33 Fuse base DIN-Rail mount

TFRD33 Fuse base DIN-Rail mount

Material

White ceramic body

Release characteristic

Super fast (FF)

Quantity

25

Voltage rating

500 V

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia