Laserliner

MaxView Camera



Camera unit VideoFlex with large depth of field and high intensity LEDs

- **Camera unit for VideoFlex**
- **Large camera head for good view due to large depth of field**
- **4 high-performance, high-intensity LEDs on the camera for powerful object lighting**
- **For inspecting highly inaccessible locations such as cavities, shafts, masonry or in vehicles**
- **Waterproof camera head and cable**
- **Compatible with G3/G4**









TECHNICAL SPECIFICATIONS

CAMERA TYPE	CMOS image sensor
CAMERA HEAD	ø 17 mm
CAMERA HEAD PROTECTION CLASS	water-resistant, IP 67
CAMERA HEAD LEDS	4
CAMERA RESOLUTION	640 x 480 pixels
FIELD OF VIEW (FOV)	57°
CAMERA FOCUS	F2 cm - F30 cm
CABLE DIAMETER	9,5 mm
LENGTH OF FLEX CABLE	1,5 m
MINIMUM BENDING RADIUS	75 mm
OPERATING CONDITIONS	0°C … 60°C, max. humidity 20 … 90% rH, no condensation, max. working altitude 4000 m above sea level
STORAGE CONDITIONS	-20°C … 80°C, max. humidity 80% rH
DIMENSIONS (W X H X D)	1580 mm x 18 mm x 18 mm
WEIGHT	298 g

MaxView Camera	**ORDER NO.** 082.217A	**EAN-CODE** 4021563707461	**PU** 1

UMAREX GmbH & Co. KG • Donnerfeld 2 • 59757 Arnsberg • Germany • Tel. +49 2932 638-300 • Fax +49 2932 638-333 • info@laserliner.com • www.laserliner.com