DATASHEET - T0-2-4929US/I1/SVB-SW/L-SOND804

Rotary cam switch

Part no. **T0-2-4929US/I1/SVB-SW/L-SOND804**
212322

Product name	Eaton rotary cam switch
Part no.	T0-2-4929US/I1/SVB-SW/L-SOND804
EAN	4015082123222
Product Length/Depth	107 millimetre
Product height	122 millimetre
Product width	80 millimetre
Product weight	0.396 kilogram
Certifications	CSA Certified UL Listed
Product Tradename	None
Product Type	Rotary cam switch
Product Sub Type	None
Actuator color	Black
Actuator type	Door coupling rotary drive
Degree of protection	NEMA 12
Degree of protection (front side)	IP65
Device construction	Complete device in housing
Electrical connection type of main circuit	Screw connection
Number of switches	1
Rated conditional short-circuit current (Iq)	6 kA
Rated operating voltage (Ue) - min	690 V
Rated operational power at AC-23A, 400 V, 50 Hz	5.5 kW
Rated operational power at AC-3, 380/400 V, 50 Hz	5.5 kW
Rated operational voltage (Ue) at AC - max	690 V
Rated permanent current at AC-21, 400 V	20 A
Rated short-time withstand current (Icw)	0.32 kA
Rated uninterrupted current (Iu)	20 A
Switching power at 400 V	5.5 kW

© 04/2023 by Eaton Industries GmbH