DATASHEET - FAZ-XAA-NA12-110VAC

Shunt release, up to 63A, 12-110V

Part no. **FAZ-XAA-NA12-110VAC**
102037

Powering Business Worldwide

General specifications

Product name	Eaton Distribution parts
Part no.	FAZ-XAA-NA12-110VAC
EAN	4015081019281
Product Length/Depth	105 millimetre
Product height	75.5 millimetre
Product width	17.7 millimetre
Product weight	0.11 kilogram
Compliances	RoHS conform
Certifications	CE marking UL (File No. E257181) UL (Category Control Number DIHS, DIHS7) North America (UL listed, CSA certified) CSA (Class No. 1437-01) CSA-C22.2 No. 5-09 CSA (File No. 204453) UL 489 IEC/EN 60898 IEC 61373 EN45545-2
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes

Product Specification Details

Accessory/spare part type	Shunt release
Additional equipment required	Shunt release (for power circuit breaker)
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for 110-V systems
Assembly width	1
Degree of protection	UL/CSA Type: - IP20 (IEC) IP40
Device fitting	Miniature circuit breaker (MCB)
Enclosure width	105 mm
Frame	Standard front dimension: 45 mm
Frequency rating	50 Hz / 60 Hz
Functions	Shunt release (for power circuit breaker)
Mounting width	17.5 mm (1 space unit)
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	1
Number of switches (fault signal)	0
Rated operational voltage (Ue) - max	110 V
Rated switch current	0 A
Suitable for current of main contact unit - max	0 A
Terminal protection	Busbar tag shroud to BGV A3
Terminal type	Twin-purpose terminals
Type	Accessory Accessory for miniature circuit breaker

Used with			Shunt releases Accessory Accessory for miniature circuit breaker
Voltage range			12 V AC - 110 V AC
Voltage type			AC/DC

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss10.0.1-27-14-35-02 [AKE327013])

Device fitting			Miniature circuit breaker (MCB)
Additional equipment			Shunt release (for power circuit breaker)
Installed at the factory			No
Width in number of modular spacings			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	110
Voltage type for actuating			AC/DC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	0

© 04/2023 by Eaton Industries GmbH