Sicherheitsadapter
- zum Adaptieren von fünf Ø 4 mm Sicherheitsmessleitungen auf CEE-Wechselstromsteckdosen
- Ø 2 mm Sicherheitsbuchse für Pilot-Kontakt
- für CEE-Steckvorrichtungen 63 A
- Bemessungsspannung der Ø 4 mm Buchsen 36 A
- Pilotkontakt ermöglicht die gemäß DIN EN 60309 und VDE 0623 vorgeschriebene elektrische Verriegelung
- den Warnhinweis WH 054 finden Sie unter www.schuetzinger.de
- für eine fachgerechte Anwendung unserer Produkte müssen die Sicherheitshinweise in unserem Katalog beachtet werden

Best.-Nr. SA 9225 / 63A
- Kontaktteile **Messing**

WH 054

Safety adapter
- *to adapt five Ø 4 mm safety measuring leads to CEE AC sockets*
- *Ø 2 mm safety socket for pilot contact*
- *for CEE connector systems 63 A*
- *Rated voltage of Ø 4 mm sockets 36 A*
- *Pilot contact enables according to DIN EN 60309 and VDE 0623 mandatory electrical interlock*
- *please visit www.schuetzinger.de fo find the warning notice WH 054*
- *for a professional application of our products, the safety instructions in our catalogue must be observed*

Order No. SA 9225 / 63A
- *contact parts* ***brass***

WH 054





Allgemeine Angaben	
Best.-Nr.	**SA 9225 / 63A** Kontaktteile Messing
Technische Daten	
Anschluss	Sicherheitsbuchse (5x)
Durchgangswiderstand	10 mΩ
Bemessungsspannung[2) 13)]	415 V CAT IV
Bemessungsstrom[2)]	36 A
Betriebstemperatur	von 0 °C bis +60 °C

General information	
Order No.	***SA 9225 / 63A*** *contact parts brass*
Technical data	
terminal	*safety socket (5x)*
transition resistance	*10 mΩ*
rated voltage[2) 13)]	*415 V CAT IV*
rated current[2)]	*36 A*
operating temperature	*from 0 °C to +60 °C*

[2)] bei normalen Umgebungstemperaturen
[13)] Bemessungsspannung der Pilot-Buchse: 250 V CAT III

[2)] *at normal ambient temperatures*
[13)] *rated voltage of pilot contact: 250 V CAT III*