DATASHEET - EMT62-DB

Thermistor overload relays for machine protection, 2 N/O, 24 - 240 V 50 - 400 Hz, 24 - 240 V DC, with reclosing lockout, with 2 sensor circuits

Part no. **EMT62-DB**
171890

General specifications	
Product name	Eaton Moeller® series EMT6 Thermistor overload relay
Part no.	EMT62-DB
EAN	4015081685158
Product Length/Depth	103 millimetre
Product height	83 millimetre
Product width	23 millimetre
Product weight	0.153 kilogram
Certifications	CSA CSA Class No.: 3211-03 UL Category Control No.: NKCR CE UL EN 55011 CSA-C22.2 No. 14 UL File No.: E29184 IEC/EN 61000-4-3 IEC/EN 60947 IEC/EN 61000-4-2 UL 508 CSA File No.: 12528 VDE 0660 IEC/EN 60947-8
Product Tradename	EMT6
Product Type	Thermistor overload relay
Product Sub Type	None
Features & Functions	
Electric connection type	Screw connection
Fitted with:	2 sensor circuits
Functions	Notifications of mains and faults via LED display Manual reset External reset possible Test function via separate button Manual or remote resetting
Temperature measuring range - min	0 °C
Temperature measuring range - max	0 °C
General information	
Degree of protection	IP20
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product category	EMT6 thermistor overload relay for machine protection
Protection	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	6000 V AC
Safe isolation	250 V AC, Between the contacts and power supply, According to EN 61140 250 V AC, Between the contacts, According to EN 61140
Shock resistance	10 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Voltage type	AC/DC
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	60 °C
Ambient operating temperature (enclosed) - min	25 °C
Ambient operating temperature (enclosed) - max	45 °C
Ambient storage temperature - min	45 °C
Ambient storage temperature - max	85 °C

Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Electro magnetic compatibility	
Air discharge	8 kV
Burst impulse	According to IEC/EN 61000-4-4 1 kV, Signal cable 2 kV, Supply cable
Contact discharge	6 kV, Electrostatic discharge (ESD)
Electromagnetic fields	1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 80 - 1000 MHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
Immunity to line-conducted interference	10 V (according to IEC/EN 61000-4-6)
Radio interference class	Class B (EN 55011)
Surge rating	2 kV, symmetrical, power pulses (Surge), EMC 4 kV, asymmetrical, power pulses (Surge), EMC According to IEC/EN 61000-4-5, power pulses (Surge), EMC
Terminal capacities	
Terminal capacity	2 x (0.5 - 1.5) mm^2, flexible with ferrule 20 - 14 AWG, solid or stranded 1 x (0.5 - 2.5) mm^2, solid 1 x (0.5 - 2.5) mm^2, flexible with ferrule 2 x (0.5 - 1.5) mm^2, solid
Screw size	M3.5, Terminal screw
Screwdriver size	2, Terminal screw, Pozidriv screwdriver 1 x 6 mm, Terminal screw, Standard screwdriver
Tightening torque	1.2 Nm, Screw terminals
Electrical rating	
Conventional thermal current ith of auxiliary contacts (1-pole, open)	6 A
Pick-up voltage	0.85 - 1.1 V x U#
Power consumption	3.5 VA at AC 2 W at DC
Rated control supply voltage (Us) at AC, 50 Hz - min	24 V
Rated control supply voltage (Us) at AC, 50 Hz - max	240 V
Rated control supply voltage (Us) at AC, 60 Hz - min	24 V
Rated control supply voltage (Us) at AC, 60 Hz - max	240 V
Rated control supply voltage (Us) at DC - min	24 V
Rated control supply voltage (Us) at DC - max	240 V
Rated insulation voltage (Ui)	240 V
Rated operational current (Ie)	3 A at AC-14, 380 V 400 V 415 V (NO) 3 A at AC-14, 400 V (NC) 3 A at AC-15, 220 V 230 V 240 V 3 A at AC-15, 220 V 230 V 240 V (NO) 1 A at AC-15, 380 V 400 V 415 V (NO)
Rated operational voltage (Ue) - max	240 V
Reset resistance	1600 O
Short-circuit protection rating	Max. 6 A gG/gL, Fuse, Contacts
Trip resistance	3600 O
Voltage rating - max	600 V
Contacts	
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	2
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	1 W

Technical data ETIM 9.0

Relays (EG000019) / Temperature monitoring relay (EC001446)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Monitoring equipment (low-voltage switch technology) / Temperature monitoring equipment (ecl@ss13-27-37-18-10 [AKF104019])			
Type of electric connection			Screw connection
With detachable clamps			No
Voltage type (supply voltage)			AC/DC
Supply voltage AC 50 Hz		V	24 - 240
Supply voltage AC 60 Hz		V	24 - 240
Supply voltage DC		V	24 - 240
Number of measuring circuits			2
Error registration possible			No
External reset possible			Yes
Temperature measuring range		°C	0 - 0
Resistance measuring range		Ohm	750 - 12000
Connection type auxiliary circuit			Screw connection
Number of contacts as normally closed contact			0
Number of contacts as normally open contact			2
Number of contacts as change-over contact			0
Voltage type (operating voltage)			AC/DC
Operating voltage AC 50 Hz		V	24 - 240
Operating voltage AC 60 Hz		V	24 - 240
Operating voltage DC		V	24 - 240
Rated switch current		A	6
Width		mm	23
Height		mm	83
Depth		mm	103

© 04/2023 by Eaton Industries GmbH