Specifications

Eaton 266694



Catalog Number: 266694

Eaton Moeller series NZM - Molded Case Circuit Breaker. Remote operator, 220-250VAC, for size 4

General specifications

Product Name
Eaton Moeller series NZM remote operator

Catalog Number
266694

EAN
4015082666941

Product Length/Depth
189 mm

Product Height
202 mm

Product Width
210 mm

Product Weight
6.1 kg

Compliances
UL/CSA
IEC
RoHS conform

Certifications
CSA (File No. 22086)
UL489
CSA (Class No. 1437-01)
CSA certified
UL (Category Control Number DIHS)
CSA-C22.2 No. 5-09
UL (File No. E140305)
CE marking
IEC60947
UL listed

Powering Business Worldwide

Product specifications

Used with

N(S)4(-4)

NZM4(-4)

Type

Accessory Remote operator, can be synchronized

Special features

Cannot be combined with switch-disconnector PN... Do not install M22-CK11(20/02) dual auxiliary contacts in the right-hand side auxiliary contact slot in NZM4-XR

Voltage rating

220 - 250 V DC

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM4

Drawings

eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps

eaton-circuit-breaker-remote-operator-nzm-remote-operator-dimensions-003.eps

eCAD model

ETN.266694.edz

Installation instructions

eaton-nzm4-romete-operator-xr-il01210006z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CS-nzm4_xr

DA-CD-nzm4_xr

Technical data sheets

eaton-nzm-technical-information-sheet

evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM4

Breaking time

3000 ms

Closing delay

100 ms

Voltage type

AC

Lifespan, mechanical

10000 operations

Number of poles

Three-pole/Four-pole

Number of operations per hour - max

20

Voltage tolerance - max

1.1

Voltage tolerance - min

.85

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

Rated control supply voltage (Us) at DC - max

250 V

Rated control supply voltage (Us) at DC - min

220 V

Signal duration of remote operator at switch off - min

500 ms

Signal duration of remote operator at switch on - min

30 ms

Switch drive type

Motor drive

Terminal capacity (solid/flexible conductor)

18 - 14 AWG

0.75 mm^2 - 2.5 mm^2 with ferrule

Operating voltage - max

1.1 x Us

Operating voltage - min

0.85 x Us

Power consumption

250 W (24 - 30 V DC)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia