ADIS08060

Inner door, 800x600

Displays and indicators can be mounted, on a surface within the enclosure while covering other components, and preventing unauthorized access.



CHARACTERISTICS	
Note	Inner doors, 400 pre-grained stainless steel
Height	800 mm
Width	600 mm
No Locks	2
Inner door dimensions Height	745 mm
Inner door dimensions Width	492 mm

Item no.: ADIS08060
EAN no.: 8713574174894

Technical data

Description: For controls, meters, lamps, etc. Hinges can be mounted to allow left or right hand opening (Machining is required). Double-bit 3 mm lock, 800 mm high doors and above have 2 locks. Usable depth between inner and external door: 35 mm, adjustable depth position with AMG accessory. Workable area: H-55, W-108. 19" version available on request.

Material: Door 1.5 mm AISI 304 stainless steel and vertical top and bottom profiles 2 mm, AISI 304 stainless steel.

Protection: IP 2XC.

Finish: 400 pre-grained stainless steel.

Pack quantity: Inner door, two vertical profiles, top and bottom profiles and mounting accessories.

Features

Feature: A plain door to be mounted inside a wall mounted enclosure.

Advantage: Additional mounting surface providing two levels of access.

Benefit: Non authorized personnel have access to the controls on the inner door only.

Comment: This accessory is often used in combination with a glazed door (ADCS).