TS4-TF4 series

Top plate castors for loads up to 265kg

A	B	C	D		Wheel Type		Swivel		Fixed	
							Catalogue reference		Catalogue reference	
3" **75**	114	73	32	80	**RUBBER TYRED**		**TS4 075 RU04**	1.24	**TF4 075 RU04**	0.86
			25	175	**REVVOTHANE**		**TS4 075 PT04**	1.21	**TF4 075 PT04**	0.83
			25	175	**REVVOTHANE**		**TS4 075 PT14**	1.40	**TF4 075 PT14**	1.00
			25	175	**REVVOTHANE**		**TS4 075 PT24**	1.55	**TF4 075 PT24**	1.18
			35	160	**NYLON**		**TS4 075 NY04**	0.91	**TF4 075 NY04**	0.53
			35	170	**NYLON**		**TS4 075 NY14**	0.95	**TF4 075 NY14**	0.59
			38	190	**REVVOPLAST**		**TS4 075 RP04**	0.98	**TF4 075 RP04**	0.60
			34	190	**CAST IRON**		**TS4 075 CI04**	1.44	**TF4 075 CI04**	1.14
			34	135	**CAST IRON**		**TS4 075 CI14**	1.61	**TF4 075 CI14**	1.30
4" **100**	139	91	35	135	**RUBBER TYRED**		**TS4 100 RU04**	1.69	**TF4 100 RU04**	1.28
			35	180	**RUBBER TYRED**		**TS4 100 RU14**	1.89	**TF4 100 RU14**	1.46
			32	225	**GREEN RUBBER**		**TS4 100 GR1E**	1.15	**TF4 100 GR1E**	0.73
			29	250	**REVVOTHANE**		**TS4 100 PT04**	1.80	**TF4 100 PT04**	1.41
			29	250	**REVVOTHANE**		**TS4 100 PT14**	1.80	**TF4 100 PT14**	1.41
			35	225	**NYLON**		**TS4 100 NY04**	1.01	**TF4 100 NY04**	0.64
			35	225	**NYLON**		**TS4 100 NY14**	1.05	**TF4 100 NY14**	0.68
			38	250	**CAST IRON**		**TS4 100 CI04**	1.41	**TF4 100 CI04**	1.37
			38	160	**CAST IRON**		**TS4 100 CI14**	1.90	**TF4 100 CI14**	2.52
5" **125**	164	105	38	160	**RUBBER TYRED**		**TS4 125 RU04**	2.20	**TF4 125 RU04**	1.82
			38	200	**RUBBER TYRED**		**TS4 125 RU14**	2.28	**TF4 125 RU14**	1.90
			32	180	**GREEN RUBBER**		**TS4 125 GR1E**	1.35	**TF4 125 GR1E**	1.93
			35	180	**NYTHANE**		**TS4 125 NT04**	1.12	**TF4 125 NT04**	0.80
			35	250	**NYTHANE**		**TS4 125 NT14**	1.13	**TF4 125 NT14**	0.89
			35	265	**REVVOTHANE**		**TS4 125 PT04**	2.05	**TF4 125 PT04**	1.69
			35	265	**REVVOTHANE**		**TS4 125 PT14**	2.18	**TF4 125 PT14**	1.81
			35	265	**NYLON**		**TS4 125 NY04**	1.10	**TF4 125 NY04**	0.73
			35	265	**NYLON**		**TS4 125 NY14**	1.14	**TF4 125 NY14**	0.77
			38	265	**CAST IRON**		**TS4 125 CI04**	2.13	**TF4 125 CI04**	1.76
			38	265	**CAST IRON**		**TS4 125 CI14**	2.22	**TF4 125 CI14**	1.86

STANDARD TOP PLATE



TS4 /TF4 top plates have fixing holes to suit 10mm diameter bolts



T19 TOP PLATE

Swivel castors only

Alternative top plate. Fixing holes to suit 8mm diameter bolt

Add suffix **T19** to catalogue reference



T03 TOP PLATE

Alternative top plate. Fixing holes to suit 8mm diameter bolt

Add suffix **T03** to catalogue reference





TS4 series castors can be fitted with rubber head seals in order to prevent the ingress of dirt and dust. Add suffix **S** to catalogue reference

WHEEL LOCK (W)

Swivel castors only

A simple hand operated parking lock

Add suffix **W** to catalogue reference



FOOTBRAKE (H)

100, 125mm swivel castors only

The foot operated pedal locks wheel

Add suffix **H** to catalogue reference



SWIVEL AND WHEEL LOCK (L)

100, 125mm swivel castors only

The foot pedal locks both wheel & swivel

Add suffix **L** to catalogue reference



THREADGUARDS (T)

100, 125mm only

Prevent string, thread etc from binding wheel

Add suffix **T** to catalogue reference



TEL +44 (0)1202 484211 FAX +44 (0) 1202 477896