Specifications

Eaton 216649



Catalog Number: 216649

Eaton Moeller® series M22 Pushbutton, RMQ-Titan, Extended, momentary, Blue, Blank, Bezel: titanium

General specifications

Product Name
Eaton Moeller® series M22 Pushbutton

Catalog Number
216649

EAN
4015082166496

Product Length/Depth
30 mm

Product Height
35 mm

Product Width
30 mm

Product Weight
0.012 kg

Compliances
CE Marked

Certifications
EN 60947-5
CSA Std. C22.2 No. 94-91
UL 508
IEC 60947-5
CSA Std. C22.2 No. 14-05
VDE
CE
VDE 0660
CSA-C22.2 No. 14-05
CSA File No.: 012528
CSA-C22.2 No. 94-91
IEC/EN 60947
UL Category Control No.: NKCR
CSA Class No.: 3211-03
IEC/EN 60947-5
UL
CSA
UL File No.: E29184
DNV
GL

Powering Business Worldwide

Features & Functions

Bezel color

Titanium

Bezel material

Plastic

Design

Extended

Classical

Fitted with:

Front ring

Inscription

Blank

General

Degree of protection

IP69K

NEMA 13

NEMA 4X

IP67

NEMA 3R

IP66

NEMA 12

Degree of protection (front side)

NEMA 4X

IP67/IP69K

Lifespan, mechanical

5,000,000 Operations

Opening diameter

22.5 mm

Operating frequency

3600 Operations/h

Product category

RMQ-Titan

Size

Front dimensions: 22 x 22 mm

Type

Pushbutton actuator

Ambient conditions, mechanical

Mounting position

As required

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Ambient storage temperature - min

40 °C

Ambient storage temperature - max

80 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Communication

Connection to SmartWire-DT

With SWD-RMQ connections

Yes

Actuator

Actuating force

5 N

Actuator color

Blue

Actuator function

Momentary

Spring-return

Contacts

Force for positive opening - min

0 N

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

Flip catalog - Product Range Catalog - Command and indication

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004157.pdf

DA-DC-00004135.pdf

Drawings

eaton-operating-pushbutton-m22-dimensions.eps

eaton-operating-pushbutton-m22-dimensions-005.eps

eaton-operating-button-symbol-003.eps

eaton-general-m22-standards.eps

eaton-operating-samrtwire-m22-3d-drawing-002.eps

eaton-general-approval-m22-symbol.eps

eaton-general-m22-symbol.eps

eCAD model

ETN.216649.edz

Installation instructions

IL04716002Z

Installation videos

RMQ Flat Design

mCAD model

DA-CD-drucktaste_hoch

DA-CS-drucktaste_hoch

Multimedia

RMQ small E-Stop emergency-stop button

MCI MultiColor Light Indicator RMQ compact solution

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

MCI Multicolor Light Indicator M22 with SmartWire-DT

Sales notes

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia