HIRSCHMANN® Test & Measurement
A BRAND OF SKS

SKS Kontakttechnik GmbH


Sockets

4 mm safety system

SEB 2630 S1,9



CE

Product	SEB 2630 S1,9
description	Safety built-in socket, 4mm diameter, contact-protected, with 1.9mm soldering spike, gold-plated brass.For installation into switchpanels and equipment chassis with wall thicknesses up to 6mm. Soldering spike can be soldered into printed boards. Installation hole: 12.2 mm diameter. Accessory: assembly tool MW SEB Tightening torque: 50Ncm
operating instruction	BA451
article-no. / *colour	9723591xx 00 black, 01 red, 02 blue, 03 yellow, 04 green, 05 brown, 06 gray, 07 white, 09 violet, 88 yellow green Au
drawing	
	
technical data	
connection	solder connection
rated voltage	AC/DC 1000 V
measurement cat. acc. to IEC 61010	CAT III
rated current (consider derating curve)	24 A
material socket	brass, gold plated
housing material	PA
temperature range acc. To IEC61010(1)	-40 °C to +80 °C

inflammability class acc. to UL 94 (only valid for basic material of housing)	V-2

(1) contact the manufacturer for applications at deviating temperature ranges
stand: 21.06.2022

stand: 21.06.2022