Junction Box

Abox 025-2,5²



Abox 025-2,5²

Junction Box

CUSTOMIZABLE

Productnumber: 80240701
Dimensions: 80 x 80 x 52 mm

Junction Box, with protection class IP65, Nominal cross-section 2.5 mm², Ui=690V AC, certified according to VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22)), Self-sealing, flexible insertion membranes, M20, Sealing area 2 - 16 mm, (1 Rear, 7 Side), Internal fastening points, for standard indoor installations

grey, with screw terminal, 5-pole - 2.5 mm² (4 x 1.5² / 4 x 2.5²)

IP65 | 2,5² | 690V AC | IK07

To industrial product:
https://www.spelsberg.com/p/49040201

Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Rated insulation voltage AC:	690 V
Max. conductor cross section:	2,5 mm²
Protection class:	II
Type of protection:	IP65
UL Type Rating:	not specified

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	80 mm
Length:	80 mm
Height:	52 mm

Material characteristics

suitable for exterior use:	no
Industry quality:	no
Halogen free:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C

Created at 20.09.2022. All statements without guarantee. We reserve the right to make improvements to technical progress.
Günther Spelsberg GmbH + Co. KG
Im Gewerbepark 1 · D-58579 Schalksmühle · Telefon: +49 (0) 23 55 / 892-0 · Telefax: +49 (0) 23 55 / 892-299

mechanical properties

for sealing range max:	16 mm
Type of fastening:	Wall/ceiling mounting
Impact strength:	IK07
Sealable:	yes
Cover screw torque:	1 Nm
for sealing range min:	2 mm

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Polystyrene
Cover material:	Polystyrene
Cover screw material:	Stainless steel V2A

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))

Accessories

84000401 - Abox 025/040 KLS-2,5²/4² - Terminal block

19202001 - KS M20 - Combi set

20342001 - WST M20 - Twist plug

21342001 - WNI M20 - Twist nipple

21642001 - SNI M20 - Stepped nipple

22742001 - KVR M20-MGM - Cable gland

22742101 - KVR M20-GDB/MGM - Cable gland

23042001 - AST M20 - Attachment bushes

23142001 - VST M20 - Sealing plugs

26012001 - DMS M20/w - Double-membrane seals

26042001 - DMS M20 - Double-membrane seals

26202001 - BST M20/sw - Ventilation seal

26242001 - BST M20 - Ventilation seal

28842001 - RST M20 - Conduit connector

89001001 - Abox PST - Sealing kit

Cable gland

