Date: 12/04/2023

TCS2BA - 40 ... 100°C G 1/2 A male 1/2 -14 NPT-F

compact temperature switch

Item number: 48784792

Quantity: 1 pcs.

Order code: TCS2BA-CADC-GASZZZABZZZ ZCK
C007000IZZZZZZZZ

Overview:
TCS2BA - 40 ... 100°C G 1/2 A male 1/2 -14 NPT-F
compact temperature switch TCS
switch enclosure: aluminium,copper-free
sensor version: direct mounting
contact version: 1xSPDT, silver contact
setting range: 40 ... 100°C, working range -40 ... +120°C, proof temperature +140°C
Set point definition: Set Point customer-specifically configured
Process connection: G 1/2 A male
Electrical connection: 1/2 -14 NPT-F
Mounting: standard direct or wall mounting, fixing bore on the case
Sensor Dimensions: active length X = 65 mm, stem diameter D=9,5 mm
Stem length for direct mounting: standard 125 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Specifications according to data sheet: TV 31.64
Repeatability of set point: ≤ 1% of span
1. set point: 70.00 °C increasing,

Details:
compact temperature switch
model TCS
Specifications according to data sheet: TV 31.64
Repeatability of set point: ≤ 1% of span
switch enclosure: aluminium,copper-free
sensor version: direct mounting
1xSPDT, silver contact
40 ... 100°C, working range -40 ... +120°C, proof temperature +140°C
Set Point customer-specifically configured
Process connection: G 1/2 A male
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Stem length for direct mounting: standard 125 mm
Sensor Dimensions: active length X = 65 mm, stem diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Unit: °C
TCS2BA
1. set point: 70.00 °C increasing,

© 2023 - WIKA Instruments s.a.r.l.