TX700 HMI/PLC Series
Quad-Core IOT Gateway — CODESYS V3 PLC with WEB VISU
DIN Rail Device for the Control Cabinet
TX700Q-P3WV01





- 3 RJ45 Ethernet ports with 10/100 Mbit
- 1 serial interface (RS232, RS485, RS422)
- 2 USB host ports
- 1 SD card slot

ID	100009355
Controller	
Processor	ARM Cortex A9, Quad-core 800 MHz
Memory	8 GB Flash
RAM memory	2048 MB
Add-on memory	1x SD card slot, 2 USB host ports
Real time clock	yes (battery-backed)
PLC data	
Programming	CODESYS V3
Released for CODESYS version	V 3.5.12.10
Programming languages	IEC 61131-3 (IL, LD, FBD, SFC, ST)
Programming interface	Ethernet
Program memory	20000 kByte
Non-volatile memory	63 kByte
Interfaces	
Onboard	3 × RJ45 Ethernet, 1 × RS232/485/422, 2 × USB host, 1 × power supply, 2 × expansion slot
Onboard for selection	CANopen Master (via extension module)
Ethernet	ETH0 - 10/100/1000 Mbit ETH1 - 10/100 Mbit ETH2 - 10/100 Mbit
Protocols	PROFINET (Controller/Device) EtherNet/IP (Scanner/Master) Modbus TCP (Master/Slave) EtherCAT (Master)
Fieldbus	Modbus RTU (Master/Slave) CANopen (Master)
USB	2 × host ports
Serial	RS232 / RS485 / RS422
Expansion slot	Two slots for up to four plug-in modules

Edition • 2024-02-02T15:52:26+01:00

Power supply	
Rated value	24 VDC, max. 0.55 A
Admissible voltage range	10…32 VDC

General data	
Operating ambient conditions	-20…60 °C, 5…85 % relative humidity, non-condensing
Storage ambient conditions	-30…70 °C, 5…85 % relative humidity, non-condensing
Approvals	CE cULus
Ex approval	ATEX IEC Ex Haz. Loc. Class I, Division 2, Groups A,B,C and D
Protection class	IP20

Dimensions	
Front (W x H x D)	44 x 174 x 144 mm
Weight	approx. 0.65 kg

Edition • 2024-02-02T15:52:26+01:00

Connection and pin assignment

	**Power Supply** The power supply connector is delivered with each device. 7/8” male receptacle for enclosure (example): RSF 40-1M W/LN Ident. no. U-36648	Pin Assignment 
	**USB Interface**	Pin Assignment 
	**Ethernet** Ethernet ports ETH1 and ETH2 (10/100 Mbit) The Ethernet ports are independent but can be bridged with ETH0. Ethernet cordsets (examples): **RJ45-RJ45:** RJ45S RJ45S 441-2M Ident. no. U-06842 **RJ45-M12 D-code:** RSSD RJ45S 441-2M Ident. no. U3-00525 **RJ45-M8:** PSGS 4M RJ45S 4413-2M Ident. no. U2-24205 **RJ45-M12 D-code female receptacle:** RJ45S FKSDED 441-1M Ident. no. U-03569	Pin Assignment  1 = TX + 2 = TX – 3 = RX + 4 = n.c. 5 = n.c. 6 = RX – 7 = n.c. 8 = n.c.
	**Ethernet** Ethernet port ETH0 (10/100 Mbit)	Pin Assignment  1 = TX + 2 = TX – 3 = RX + 4 = n.c. 5 = n.c. 6 = RX – 7 = n.c. 8 = n.c.

Edition • 2024-02-02T15:52:26+01:00

	**Serial Interface** The serial interface can be operated either as RS232, RS485 or RS422. The adjacent wiring diagrams show the respective pin assignments. **PLEASE NOTE:** In RS485 mode, pins 1 and 2 as well as 3 and 4 must be externally connected!	Pin assignment in RS232 operating mode  1 = RX 2 = TX 3 = CTS 4 = RTS 5 = +5 VDC output 6 = GND 7 = n.c. 8 = shield Pin assignment in RS485 operating mode  1 = B- (RX-) 2 = A- (TX-) 3 = B+ (RX+) 4 = A+ (TX+) 5 = +5 VDC output 6 = GND 7 = n.c. 8 = shield Pin assignment in RS422 operating mode  1 = RX- 2 = TX- 3 = RX+ 4 = TX+ 5 = +5 VDC output 6 = GND 7 = n.c. 8 = shield
	**Ports for Plug-in Modules**	
	**SD Card Slot** SD card	

Edition • 2024-02-02T15:52:26+01:00

Accessories

Type code	Ident-No.		Dimension drawing
TX-LTE-WLAN	100025179	Plug-in LTE and Wi-Fi modem with LTE/UMTS/GSM, Wi-Fi and GNSS	

Function accessories

Type code	Ident-No.		Dimension drawing
TX-IO-XX03	6828201	Plug-in I/O module — 20 DI, 12 DO, 4 AI (U/I/RTD/TC), 4 AO (U/I)	
TX-IO-DX06	6828203	Plug-in I/O module — 8 DI, 6 DO, 1 relay output (NO)	
TX-DP-S	100010167	Plug-in PROFIBUS DP slave interface, 9-pin SUB-D female connector	
TX-CAN	6828210	Plug-in CANopen interface, 9-pin SUB-D male connector	

Edition • 2024-02-02T15:52:26+01:00

Function accessories

Type code	Ident-No.		Dimension drawing
TX-RS485	100002598	Plug-in interface for RS485/RS422, 9-pin SUB-D female connector	
TX-RS232	100002599	Plug-in interface for RS232, 9-pin SUB-D female connector	
TX-PSC	100002938	Power Supply Male Connector for TX HMI Devices	