Specifications

# Eaton EBH223TBM1

## Catalog Number: EBH223TBM1

Eaton Bussmann series low voltage NH fuse base, Switch disconnector, low voltage, 400 A, AC 690 V, NH2, AC23B, 3P, IEC, 100mm busbar, bottom cable terminals, for connection of conductors with lug terminals, M10 screws




### General specifications

**Product Name**
Eaton Bussmann series low voltage NH fuse base

**Catalog Number**
EBH223TBM1

**EAN**
5027590409285

**Product Length/Depth**
215 mm

**Product Height**
330 mm

**Product Width**
190 mm

**Product Weight**
4326 g

**Compliances**
CE

**Certifications**
IEC/EN 60947-1
IEC 60947-3

Powering Business Worldwide

## Product specifications

### Type

Fuse accessory

### Application

Motor control centres, distribution boards, Cable distribution cabinets

### Amperage Rating

400 A

### Rated operational power at AC-23A, 400 V, 50 Hz

0.16 kW

### Rated permanent current (Iu)

400 A

### Rated uninterrupted current (Iu)

400 A

### Conditioned rated short-circuit current Iq

0.08 kA

### With error protection

No

### Number of poles

Three-pole

### Rated operation power at AC-23, 400 V

0.16 kW

### Rated short-time withstand current (Icw)

80 A

### Electrical connection type of main circuit

Screw connection

### Actuator position

Front side

### Actuator type

Cover grip

### Construction size

NH2

### Fuse shape

Horizontal

### Suitable for

Busbar mounting

## Resources

### Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

### Declarations of conformity

UKCA fuse switch disconnectors, EBC, EBV and EBH series

CE fuse switch disconnectors, EBC, EBV and EBH series

### Technical data sheets

10275 EBV Vertical fuse switch-disconnector

### Technical service bulletins

10293 EBH Horizontal switch-disconnector

NH2

### Suitable for fuses

NH2

### Cable entry type

Bottom

### Mounting method

60 mm busbar mounting

100 mm busbar mounting

Mounting plate

### Voltage rating

690

### Degree of protection (front side)

IP30

### Electrical connection type

Screw connection

### Rated operating voltage (Ue) at AC - max

690 V

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia