
PRODUCT-DETAILS

OS25FF2210N1

OS25FF2210N1 SWITCH FUSE



General Information

Extended Product Type	OS25FF2210N1
Product ID	1SCA108638R1001
EAN	6417019419015
Catalog Description	OS25FF2210N1 SWITCH FUSE
Long Description	Switch-disconnector fuse, 25A, 4-pole, NFC 10x38, front operated, switched non-fusible fourth pole, handle and shaft included.

ABB EcoSolutions

Environmental Product Declaration - EPD	1SCC311204D0201

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Declaration	1SCC011020D0201

© 2025 ABB. All rights reserved.

RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311030M0202
Mechanical Drawings	OS25FF2210N1.stp
Environmental Product Declaration - EPD	1SCC311204D0201

Environmental

Degree of Protection	acc. to IEC 60529 IP20
Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country or Territory of Origin	Lithuania

Dimensions

Product Net Width	142 mm
Product Net Height	97 mm
Product Net Depth / Length	105 mm
Product Net Weight	0.8 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	240 mm
Package Level 1 Depth / Length	108 mm
Package Level 1 Height	130 mm
Package Level 1 Gross Weight	0.8 kg
Package Level 1 EAN	6417019419015

Technical

Cable Cross-Section	0.75 ... 10 mm²
Connecting Capacity	Stranded 0.75 … 10 mm² Flexible 0.75 … 10 mm²
Conventional Free-air Thermal Current (I_{th})	Θ = 40 °C 25 A
Conventional Thermal Current (I_{the})	Fully Enclosed 25 A
Degree of Protection	acc. to IEC 60529 IP20
Fourth Pole Position	Left Side
Fourth Pole Type	Switched - With Solid Link
Fuse Size	10x38

© 2025 ABB. All rights reserved.

Fuse System	NFC
Handle Type	Pistol handle
Mounting Type	Base mounting
Number of Poles	4P
Operating Mode	Front
Pollution Degree	3
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Power Loss	at Rated Operating Conditions per Pole 1.3 W
Rated Conditional Short-Circuit Current (I_{nc})	(500 V) 100 kA (690 V) 80 kA
Rated Current (I_n)	Main Circuit 25 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current AC-21A (I_e)	(500 V) 25 A (690 V) 25 A
Rated Operational Current AC-22A (I_e)	(500 V) 25 A (690 V) 25 A
Rated Operational Current AC-23A (I_e)	(500 V) 25 A (690 V) 25 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 5.5 kW (400 V) 11 kW (415 V) 11 kW (500 V) 15 kW (690 V) 22 kW
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 1 kiloampere rms
Recommended Screw Driver	Main Circuit Slot
Standards	IEC 60947-3
Switches Operating Mechanism	22 (Between the Poles)
Terminal Type	Screw Terminals
Tightening Torque	2 N·m
Wire Stripping Length	Main Circuit 12...14 mm Main Circuit 0.47...0.55 in

Technical UL/CSA

Wire Stripping Length	Main Circuit 12...14 mm Main Circuit 0.47...0.55 in
Recommended Screw Driver	Main Circuit Slot
Tightening Torque	2 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC311129D2702
DNV GL Certificate	1SCC311125D0203
UL Certificate	No certification needed

External Classifications and Standards


Object Classification Code	Q

© 2025 ABB. All rights reserved.

ETIM 9	EC001040 - Fuse switch disconnector
ETIM 10	EC001040 - Fuse switch disconnector
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5291 >> Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses



© 2025 ABB. All rights reserved.