Specifications

Eaton 266608

Catalog Number: 266608

Eaton Moeller series NZM - Molded Case Circuit Breaker. Rotary handle, lockable



General specifications

Product Name
Eaton Moeller series NZM operating element

Catalog Number
266608

EAN
4015082666088

Product Length/Depth
150 mm

Product Height
80 mm

Product Width
210 mm

Product Weight
1.314 kg

Compliances
IEC
UL/CSA
RoHS conform

Certifications
UL listed
CSA (Class No. 1437-01)
UL (File No. E140305)
CSA certified
CSA (File No. 22086)
IEC60947
UL489
CSA-C22.2 No. 5-09
UL (Category Control Number DIHS)
CE marking

Powering Business Worldwide

Product specifications

Used with

NZM4(-4), N(S)4(-4)

Type

Accessory Rotary handle on circuit-breaker

Special features

Complete with rotary drive Cannot be combined with insulating surround MODAN handle position detection by wire release can be retrofitted Makes it possible to operate the switch with a rotational movement and provides locking facilities

Features

Lockable

Standard: black / gray

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM4

Drawings

eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps

eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-dimensions-004.eps

eaton-circuit-breaker-rotary-handle-nzm-rotary-handle-3d-drawing-005.eps

Installation instructions

eaton-circuit-breaker-rotary-drive-nzm4-il01210004z.pdf

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

DA-CD-nzm4_xd

DA-CS-nzm4_xd

Technical data sheets

eaton-nzm-technical-information-sheet

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

Padlock
Extension shaft

Frame

NZM4

Activation type

Rotary handle

Suitable for

Switch disconnector

Power circuit breaker

Locking facility

Lockable on the 0 position on the switch using up to 3 padlocks

Degree of protection / NEMA enclosure type

IP20

4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia