Date: 11/04/2023

ARV2"-VS-L300/12-V52A

ARV2"-VS-L300/12-V52A

Item number: 48769678

Quantity: 1 pcs.

Order code: FLS-CBMZZ001021000DA9ZZGFZZ0250SZZZZZZZZZZZZZZZZZZ
KBRVIA03001NZZZZ

Overview:
ARV2"-VS-L300/12-V52A
Float Switch Type FLS-SA
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 1 bar
Temperature range: -30°C up to 130°C
Fluid density: 1000 kg/m³
Housing: Aluminium
Ingress protection: IP66/68
Electrical connection: M16 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 2"BSP
Switch function 1: Closing on rising level (SPST) 250 mm
Switch rating: max. AC 230V; 100VA; 1A / DC 230V; 50W; 0.5A
Float: Stainless steel 316Ti V52A; Float outer diameter: 52 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 300 mm
Float stop: Float collar
Float fits through the connection nozzle
Weight: 1.2 kg

Details:
ARV2"-VS-L300/12-V52A
Float Switch Type FLS-SA
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 1 bar
Temperature range: -30°C up to 130°C
Fluid density: 1000 kg/m³
Housing: Aluminium
Ingress protection: IP66/68
Electrical connection: M16 x 1.5 mm with cable gland
Process connection: Mounting thread downwards 2"BSP
Switch function 1: Closing on rising level (SPST) 250 mm
Switch rating: max. AC 230V; 100VA; 1A / DC 230V; 50W; 0.5A
Float: Stainless steel 316Ti V52A; Float outer diameter: 52 mm
Number of floats: 1 pc
Guide tube: OD 12 mm Insertion length (L): 300 mm
Float stop: Float collar
Float fits through the connection nozzle
Weight: 1.2 kg

© 2023 - WIKA Instruments s.a.r.l.