PRODUCT-DETAILS

# E1.2B 630 Ekip G Hi-Touch LSIG 3p F F

## E1.2B 630 Ekip G Hi-Touch LSIG 3p F F



### General Information

| | |
|---|---|
| Extended Product Type | E1.2B 630 Ekip G Hi-Touch LSIG 3p F F |
| Product ID | 1SDA070710R1 |
| EAN | 8015644745608 |
| Catalog Description | E1.2B 630 Ekip G Hi-Touch LSIG 3p F F |
| Long Description | C.BREAKER SACE EMAX2 E1.2B 630 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP/G/HI-TOUCH-LSIG R 630 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED |

### ABB EcoSolutions

| | |
|---|---|
| ABB EcoSolutions | Yes |
| Environmental Product Declaration - EPD | 9AKK108468A1900<br>9AKK108468A3028 |

### Material Compliance

| | |
|---|---|
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

## Environmental

| | |
|---|---|
| Environmental Information | 9AKK108467A6707 |

## Ordering

| | |
|---|---|
| Order Code US and Canada | Z1BNEEBQ200A000000XX |
| EAN | 8015644745608 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

## Dimensions

| | |
|---|---|
| Product Net Width | 210 mm |
| Product Net Height | 296 mm |
| Product Net Depth / Length | 183 mm |
| Product Net Weight | 14 kg |

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 270 mm |
| Package Level 1 Height | 350 mm |
| Package Level 1 Depth / Length | 330 mm |
| Package Level 1 Gross Weight | 16 kg |
| Package Level 1 EAN | 8015644745608 |

## Additional Information

| | |
|---|---|
| Product Main Type | SACE Emax 2 |
| Product Name | Air Circuit Breaker |
| Product Type | Air Circuit Breaker |
| Version | F |

## Technical

| | |
|---|---|
| Current Type | AC |
| Electrical Durability | Ue =< 440 V 8000 cycle<br>Ue = 500 ... 690 V 8000 cycle<br>30 cycles per hour |
| Mechanical Durability | 20000 cycle |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| | 60 cycles per hour |
| Number of Poles | 3P |
| Power Loss | 31 W |
| Rated Current ($I_n$) | 630 A |
| Rated Impulse Withstand Voltage ($U_{imp}$) | acc. to IEC 60947-2 12 kV |
| Rated Insulation Voltage ($U_i$) | AC 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | (220 V AC) 42 kA<br>(230 V AC) 42 kA<br>(380 V AC) 42 kA<br>(400 V AC) 42 kA<br>(415 V AC) 42 kA<br>(440 V AC) 42 kA<br>(500 V AC) 42 kA<br>(660 V AC) 42 kA<br>(690 V AC) 42 kA |
| Rated Service Short-Circuit Breaking Capacity, in % of Icu ($I_{cs}$) | 100 % |
| Rated Short-time Withstand Current Low Voltage ($I_{cw}$) | for 1 s 42 kA<br>for 3 s 24 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | (400 V AC) 42 kA<br>(415 V AC) 42 kA<br>(440 V AC) 42 kA<br>(500 V AC) 42 kA<br>(525 V AC) 42 kA<br>(690 V AC) 42 kA |
| Rated Uninterrupted Current ($I_u$) | 630 A |
| Rated Voltage ($U_r$) | 690 V |
| Release | Ekip G Hi-Touch LSIG |
| Release Type | EL |
| Short-Circuit Performance Level | B |
| Standards | IEC |
| Sub-type | E1.2 |
| Suitable for IT Networks | Yes, 690V |
| Terminal Connection Type | Front |

## Certificates and Declarations

| | |
|---|---|
| Data Sheet, Technical Information | 1SDC200023D0209 |
| Declaration of Conformity - CE | 9AKK106713A5546 |
| Instructions and Manuals | 1SDH000999R0002 |
| Instructions and Manuals (Part 2) | 1SDH001316R1002 |

## Classifications

| | |
|---|---|
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| IDEA Granular Category Code (IGCC) | 4926 >> Air circuit breakers |
| Object Classification Code | Q |
| UNSPSC | 39121615 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370409 |

## Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2





© 2024 ABB. All rights reserved.