Date: 11/04/2023

MA-XXDS - 0...16 bar - Adaptor 1/2 NPT-F - 1/2 -14 NPT-F

Diaphragm pressure switch

Item number: 83124655

Quantity: 1 pcs.

Order code: MA-XXDS-BBK3B-3AMZZZZ1ZZZZZZZZZZZZZZZZZZZ ZCK3AW
F4-C5- - - - -

Overview:
MA-XXDS - 0...16 bar - Adaptor 1/2 NPT-F - 1/2 -14 NPT-F
Diaphragm pressure switch
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling
setting range: 0...16 bar
Standard, working 0…16 bar, proof 60 bar (diaphragm K and T = proof 40 bar)
Process connection: Adaptor 1/2 NPT-F
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Inconel 718/O-Ring: FPM/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point not defined

Details:
Diaphragm pressure switch
Flameproof enclosure Ex d
Model MA
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span
Contact version: 2 x SPDT or 1 x DPDT silver contact, hermetically sealed, argon gas filling
setting range: 0...16 bar
working range: Standard, working 0…16 bar, proof 60 bar (diaphragm K and T = proof 40 bar)
Set Point not defined
Unit: bar
Process connection: Adaptor 1/2 NPT-F
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66
MA-XXDS

© 2023 - WIKA Instruments s.a.r.l.

Diaphragm: Inconel 718/O-Ring: FPM/Connection: Stainless steel AISI 316L

© 2023 - WIKA Instruments s.a.r.l.