Date: 11/04/2023

TSD-30 ; -20 ... +80 °C; two switching output (PNP) + 4...20 mA

Electronic Temperature Switch with Display Model TSD-30

Item number:	48759778
Quantity:	1 pcs.
Order code:	TSD-30-Q-CA-M0100-GT1-M5-WW-ZZ W1011TS3-ZZZZZ-S3R-GSFK
Overview:	TSD-30 ; -20 ... +80 °C; two switching output (PNP) + 4...20 mA @ 15...35 V DC; Probe length: 100 mm; G 1/2 A DIN EN ISO 1179-2 (formerly DIN 3852-E) Sealing: NBR 5-pin locking plug M12 x 1 U+=1, U-=3, S+=5, SP1=4, SP2=2 Approvals: cULus Specifications according to data sheet: TE 67.03
Details:	Electronic Temperature Switch with Display Model TSD-30 Specifications according to data sheet: TE 67.03 Output signal: two switching output (PNP) + 4...20 mA Temperature range: -20 ... +80 °C Probe length unit: mm Process connection: G 1/2 A DIN EN ISO 1179-2 (formerly DIN 3852-E) Sealing: NBR Electrical connection: 5-pin locking plug M12 x 1 Approvals: cULus Pin assignment: U+=1, U-=3, S+=5, SP1=4, SP2=2 Power supply: 15...35 V DC Probe length: 100 mm

© 2023 - WIKA Instruments s.a.r.l.