Date: 11/04/2023

SC15.20.060 50 ... 150°C CL.2

Tension thermometer - Indicating temperature controller SC15

Item number:	48788396
Quantity:	1 pcs.
Order code:	SC15-ZZ20060AB20CQO1AAZZZZZZZZZB0100Z19M0850065G4Z5 ZZZZZZZZ1ZZZZZZZB2EZ
Overview:	SC15.20.060 50 ... 150°C CL.2 standard, steel case Panel mounting with clamp, triangular front ring chrome plated, with protective cap IP54 1 adjustable changeover switch, adjusting knob 5 A non-inductive at max. 250VAC 50/60Hz terminal block Capillary [FL]: 1.00 m Copper braided, 2x Supportspirales (sensor - case) Connection design: SV19 G1/2B Insertion length [L1] o. [U1]: 65 x 8,5 mm brass Dial background: White *WIKA*
Details:	Tension thermometer - Indicating temperature controller SC15 Specifications according to data sheet: TV 28.02 Model: SC15 - combistat Design: standard, steel case Nominal size [NG, d1]: 60 mm Mounting option: Panel mounting with clamp, Front ring: triangular front ring chrome plated, Ingress protection [IP]: with protective cap IP54 Unit: °C Scale range: 50 ... 150°C Contact type: 1 adjustable changeover switch, Contact adjustment: adjusting knob Switch rating: 5 A non-inductive at max. 250VAC 50/60Hz Cable connection: terminal block Capillary material: Copper braided, Capillary [FL]: 1.00 Connection design: SF91/SV19 - Connection rotatable with lose connection, Probe material: brass Probe diameter [d5] o. [F1]: 8,5 mm Insertion length [L1] o. [U1]: 65 Process connection [d6 o. E]: Male thread G1/2B Manufacturer logo: *WIKA* Accuracy class: class 2 per EN 13190 Capillary protection: 2x Supportspirales (sensor - case)

© 2023 - WIKA Instruments s.a.r.l.

Dial background: White

© 2023 - WIKA Instruments s.a.r.l.