Date: 11/04/2023

MA-XXUN - 0...200 mbar - 1/4 NPT-F - 1/2 -14 NPT-F

Diaphragm pressure switch

Item number: 48715606

Quantity: 1 pcs.

Order code: MA-XXUN-MAL3C-1AMZZZZ1ZZZZZZZZZZZZZZZZZZZ ZCK1AW
M010000DZZZZZZZZ
F4-C5- - - - -

Overview:
MA-XXUN - 0...200 mbar - 1/4 NPT-F - 1/2 -14 NPT-F
Diaphragm pressure switch
measuring elements and wetted materials: Diaphragm AISI 316, 304, Inconel or Hastelloy (Piston AISI 316)/ Process Connection AISI 316L
Contact version: 1x SPDT silver contact
setting range: 0...200 mbar
Standard, working range = 0...0,2 bar, proof pressure 6 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting
Ingress Protection: IP66
Diaphragm: Stainless Steel AISI 316/O-Ring: FPM/Connection: Stainless steel AISI 316L
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span

Set point definition: Set Point customer-specifically configured
1. set point: 100.00 mbar decreasing,

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Diaphragm pressure switch
Flameproof enclosure Ex d
Model MA
Specifications according to data sheet: PV 31.11
Repeatability of set point: ≤ 1% of span
Contact version: 1x SPDT silver contact
setting range: 0...200 mbar
working range: Standard, working range = 0...0,2 bar, proof pressure 6 bar
Set Point customer-specifically configured
Unit: mbar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
Enclosure with plate for wall or direct mounting

© 2023 - WIKA Instruments s.a.r.l.

Date: 11/04/2023

Brand: WIKA Instruments Italia
Ingress Protection: IP66
MA-XXUN
Diaphragm: Stainless Steel AISI 316/O-Ring: FPM/Connection: Stainless steel AISI 316L
1. set point: 100.00 mbar decreasing,

Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.