
TIMKEN

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number 39590 - 39520, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Basic Load Ratings | Factors

Specifications

Series	39500
Cone Part Number	39590
Cup Part Number	39520
Design Units	Imperial
Bearing Weight	1.200 Kg 2.60 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	66.675 mm 2.6250 in
D - Cup Outer Diameter	112.713 mm 4.4375 in

B - Cone Width	30.163 mm 1.1875 in
C - Cup Width	23.813 mm 0.9375 in
T - Bearing Width	30.163 mm 1.1875 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius[1]	3.560 mm 0.14 in
r - Cup Backface "To Clear" Radius[2]	3.30 mm 0.130 in
da - Cone Frontface Backing Diameter	74.93 mm 3.57 in
db - Cone Backface Backing Diameter	82.04 mm 3.23 in
Da - Cup Frontface Backing Diameter	107.95 mm 4.25 in
Db - Cup Backface Backing Diameter	101.09 mm 3.98 in
Ab - Cage-Cone Frontface Clearance	3.3 mm 0.13 in
Aa - Cage-Cone Backface Clearance	1.3 mm 0.05 in
a - Effective Center Location[3]	-6.60 mm -0.26 in


Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)[4]	43300 N 9730 lbf
C1 - Dynamic Radial Rating (1 million revolutions)[5]	167000 N 37500 lbf
C0 - Static Radial Rating	224000 N 50300 lbf
C_{a90} - Dynamic Thrust Rating (90 million revolutions)[6]	25100 N 5650 lbf

Factors

K - Factor[7]	1.72
e - ISO Factor[8]	0.34
Y - ISO Factor[9]	1.77
G1 - Heat Generation Factor (Roller-Raceway)	84.3
G2 - Heat Generation Factor (Rib-Roller End)	23.7
Cg - Geometry Factor	0.107

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These maximum fillet radii will be cleared by the bearing corners.
[3] Negative value indicates effective center inside cone backface.
[4] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.
[5] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.
[6] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.
[7] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[8] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[9] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e	0.34	
ISO Factor - Y	1.77	
Bearing Weight	2.6	lb
Number of Rollers Per Row	21	
Effective Center Location	-0.26	inch

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

39590 - 39520
TS BEARING ASSEMBLY

K Factor	1.72	
Dynamic Radial Rating - C90	43300	lbf
Dynamic Thrust Rating - Ca90	25100	lbf
Static Radial Rating - C0	224000	lbf
Dynamic Radial Rating - C1	167000	lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY