Specifications

Eaton 125NHG00B-400

Catalog Number: 125NHG00B-400

Fuse-link, LV, 125 A, AC 400 V, NH00, gL/gG, IEC, dual indicator, live gripping lugs

General specifications

Product Name
Eaton Bussmann series low voltage NH Fuse

Catalog Number
125NHG00B-400

EAN
5027590429900

Product Length/Depth
79 mm

Product Height
58 mm

Product Width
30 mm

Product Weight
201 g

Compliances
CE Marked
RoHS Compliant

Certifications
IEC 60269-1
IEC 60269-2
DIN 43620

Product specifications

Type

Fuse

Application

industrial

Utilities, Solar, Wind

Amperage Rating

125 A

Fitted with:

Metal gripping lugs

Fuse size

NH00

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

400 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Accessory/spare part type

SDL-00 Solid link

FEH- Fuse extraction handle

TD00-IP20 IP protection kit

TD00-IP20I Integral protection kit

TD00-IP20IC Integral Triple pole protection kit including fuse covers

Utilization category

gL/gG (cable protection/equipment protection)

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

NH Fuse links, bases and gear

Declarations of conformity

CE NH Size 00, 400V fuse-links

UKCA NH Size 00, 400V Size 00 fuse-links

eCAD model

eaton-low-voltage-nh-fuse-eplan-125nhg00b-400.edz

Multimedia

Eaton Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

720099 NH 400 Volts gG

Technical service bulletins

Datasheet - 125NHG00B-400

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Watt losses

7 W

Connection

Blade end

Construction

NH00

Construction size

NH00

Fuse shape

Square body

Knife blade contacts

Voltage type

AC

Suitable for

SD00-D Single pole NH Fuse base

TD00-D Tripe pole NH Fuse base

Microswitch 170H0236

EBH Size 00 to 4 Horizontal fuse switch-disconnectors

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Rated switching capacity AC

120 kA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia