Specifications

Eaton 206928



Catalog Number: 206928

Eaton Moeller® series UTI Control transformer, 0.8 kVA, Rated input voltage 208 – 600 V, Rated output voltage 2 x 115 V

General specifications

Product Name
Eaton Moeller® series UTI Control transformer

Catalog Number
206928

EAN
4015082069285

Product Length/Depth
124 mm

Product Height
150 mm

Product Width
151 mm

Product Weight
9.6 kg

Compliances
CE Marked

Certifications
VDE
CE
Certified by UL for use in Canada
UL Recognized
UL5085-1
VDE 0550
CSA-C22.2 No. 66.1-06
UL 506
UL 5085-2
IEC/EN 60204-1, ÖVE-EN 13
VDE 0113, VDE 0100 Part 410
VDE 0570 Part 2-2/2-6 (safety transformer)
VDE 0570 Part 2-4 (isolating transformer)
UL Category Control No.: XPTQ2, XPTQ8
CSA-C22.2 No. 66
CSA-C22.2 No. 66.2-06
IEC/EN 61558-2-2

Powering Business Worldwide

Features & Functions

Features

Separate windings

Fully Vacuum-impregnated

Reinforced insulation

General

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

40 °C

Connection type

Terminations

Duty factor

100 %

Insulation class

B

Primary tapping

± 20 %

Product category

Single-phase UTI multi-winding transformers

Suitable for

Branch circuits, (UL/CSA)

Electrical rating

Efficiency

92.8 %

No-load losses

33 W

Rated frequency - min

50 Hz

Rated frequency - max

60 Hz

Rated power

0.8 VA

Relative short-circuit voltage

2.8 %

Short-circuit losses

29 W

Voltage rating - max

600 V

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

62 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Resources

Application notes

eaton-transformer-stz-sti-stn-dtz-uti-ap009002-en-us.pdf

Brochures

eaton-transformers-brochure-br009002en-en-us.pdf

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Declarations of conformity

DA-DC-00004450.pdf

DA-DC-00004418.pdf

Drawings

eaton-general-transformer-uti-control-transformer-dimensions-006.eps

eCAD model

ETN.UTI0,8-115

mCAD model

uti0_8_115.stp

uti0_8_115

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia