Date: 25/04/2023

DPGS43.100...LM-D51 10 bar 2 x G 1/4 female

switchGAUGE DPGS43.100/160

Item number:	48767748
Quantity:	1 pcs.
Order code:	DPGS43.100.23ZZZPZ-BG410Z-IHAA-LM-D51-ZZZIZ-ZZZZ 5UZZZ 33DZHZZFSGZZ-ZZZZZZ11Z
Overview:	DPGS43.100...LM-D51 10 bar 2 x G 1/4 female magnetic snap action switch, model 821.3 plug sidewise Case: with pressure blowout disk Connection location: lower mount class 1.6 Ingress protection: IP 54 max. static pressure: 25 bar Overpressure safety: 25 bar laminated safety glass Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F) Permissible ambient temperature: -20 … +60 °C Pressure Gauge Standard: International (standard Europe) *WIKA* Serial number *...*
Details:	switchGAUGE DPGS43.100/160 differential pressure gauge with switches, all welded construction Specifications according to data sheet: PV 27.05 and AC 08.01 switch: magnetic snap action switch, model 821 first switch operation: change over (3) Electrical connection: plug sidewise Nominal size: 100 Scale range: 0...10 bar max. static pressure: 25 bar Overpressure safety: 25 bar Process connection: 2 x G 1/4 female Connection location: lower mount Liquid Damping (case filling): without filling Case: pressure blowout disk Pressure Gauge Standard: International (standard Europe) Accuracy class: class 1.6 Case material: Stainless steel 1.4301 Case surface: bare Window: laminated safety glass Ingress protection: IP 54 Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F) Permissible ambient temperature: -20 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.

Date: 25/04/2023

Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*

© 2023 - WIKA Instruments s.a.r.l.