Date: 06/04/2023

113.53.100 250 bar G1/2B center back mount

Pressure gauge with glycerine filling, stainless s

Item number:	7009861
Quantity:	1 pcs.
Order code:	113.53-E-BG525Z-GD-BZCZ3G-ZZZ DIAL-IAZ1ZZZZZZZZZ1Z- 1Z1ZZ41ZZZ
Overview:	113.53.100 250 bar G1/2B center back mount class 1.6 case filling: glycerine stop-pin at zero *EN 837-1* *Cl.1.6* *CE TYPE X* *WIKA*
Details:	Pressure gauge with glycerine filling, stainless s teel case, Model 113.53 Movement: copper alloy case: stainless steel ingress protection: IP 65 Bezel ring: roll formed, stainless steel Nominal size: 100 mm Unit of outer Scale: bar Measuring range: gauge pressure range Scale range: 0...250 bar Process connection: G 1/2 B Connector location: center back mount window: polycarbon Accuracy class: class 1.6 case filling: glycerine Model: 113.53 Dial description: Pressure Gauge Standard: International (standard Europe) color for 1.scale (outside): black dial background: White Manufacturer logo: *WIKA* stop pin on dial: at zero norm-mark on dial: *EN 837-1* accuracy class on dial: *Cl.1.6* CE mark on dial: *CE TYPE X*

© 2023 - WIKA Instruments s.a.r.l.