AUUM30VSL

FFP3 NR D



Use (*)

Agriculture | Maintenance | Chemical industry | Heavy industry | Light industry

Technical features

- **Designation:** Filtering face-piece respirator. Filters solid and liquid aerosols. Single-use. Conical shape. «Big eye» design. Adjustable nosepiece. Buckle adjustment. Facial foam. Exhalation valve.
- **Material:** non-woven polypropylene.
- **Color:** white.
- **Classification: FFP3 NR D.**
- **Expiry date:** if maintained as per storage instructions, product can be used up to 5 years from date of manufacture.
- **Packing:**
  - carton de 12 boxes.
  - boxes of 5 units.
  - eacht mask under individual polybag.

Learn more: ***www.singer.fr***

Advantages

- Passes EN 149:2001 optional Dolomite (D) clogging test for more comfortable breathing.
- Unique «Big Eye» design provides very low breathing resistance due to the increased filtration area.
- Polypropylene outer layer provides smooth lining and avoids loose fibers.
- Embossed fringe seal avoids fluffy open layer around the edges.
- Contour design ensures the compatibility of spectacles/goggles and reduces fogging.
- Adjustable nosepiece ensures custom shape and increases worker comfort and acceptance.
- Improved contour fit with adjustable buckles. Easy breathing/Speaking. Clear vision. Free maintenance (disposable item).
- The **ISO 9001 / ISO 14001** certified production guarantees the reliability / regularity of the production and the control of the environmental impact.

Certification

This product complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). **Category III.**
Issued by **BSI (The Netherlands).**
Notified body **n°2797.**

EN 149 : 2001 + A1: 2009

EN149: requirements	FFP1	FFP2	**FFP3**
Total inward leakage	< 22%	< 8%	**< 2%**
Maximum penetration of test aerosol (Sodium chloride or paraffin oil)	< 20%	< 6%	**< 1%**
Breathing resistance			
- inhalation (30 l/min)	< 0,6 mbar	<0,7 mbar	**< 1,0 mbar**
- inhalation (95 l/min)	< 2,1 mbar	< 2,4 mbar	**< 3,0 mbar**
- exhalation (160 l/min)	< 3,0 mbar	< 3,0 mbar	**< 3,0 mbar**

CE 2797
EN 149: 2001+A1: 2009

Download the EU declaration of conformity on **http://docs.singer.fr**

(*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use.
Before any use, read carefully the instructions enclosed with the product. Issue LS_2021_04_22 / **Copyright Singer® Safety**

SINGER safety