Date: 12/04/2023

TCA2BA - 70 ... 120 °C - 1/2 NPT male - Electrical connection: 1/2 - 14 NPT-F

compact temperature switch

Item number: 14160376

Quantity: 1 pcs.

Order code: TCA2BA-CAEB-EASZZZAD1ZZ ZCK
F5-C5- - - - -

Overview:
TCA2BA - 70 ... 120 °C - 1/2 NPT male - Electrical connection: 1/2 -14 NPT-F
compact temperature switch TCA
switch enclosure: aluminium,copper-free
sensor version: direct mounting
contact version: 1xSPDT, silver contact
setting range: 70 ... 120°C, working range -40 ... +170°C, proof temperature +180°C
Set point definition: Set Point not defined
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
Mounting: standard direct or wall mounting, fixing bore on the case
Stem length for direct mounting: standard 125 mm
Sensor Dimensions: active length X = 55 mm, stem diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Specifications according to data sheet: TV 31.65
Repeatability of set point: ≤ 1% of span

Details:
compact temperature switch
model TCA
Specifications according to data sheet: TV 31.65
Repeatability of set point: ≤ 1% of span
switch enclosure: aluminium,copper-free
sensor version: direct mounting
1xSPDT, silver contact
70 ... 120°C, working range -40 ... +170°C, proof temperature +180°C
Set Point not defined
Process connection: 1/2 NPT male
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Stem length for direct mounting: standard 125 mm
Sensor Dimensions: active length X = 55 mm, stem diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Unit: °C
TCA2B

© 2023 - WIKA Instruments s.a.r.l.