KombiSIGN 50 / Buzzer Devices 849

# Buzzer element contin/pulse 230VAC BK



| | |
|---|---|
| **Part No.:** | **849.000.68** |
| **Series:** | **KombiSIGN 50** |

| MECHANICAL DATA | |
|---|---|
| Height | 72 mm |
| Diameter | 52 mm |
| Materials | PC |
| Housing colour | Black |
| Protection category | IP54 |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 64.1 g |
| Product weight | 53.5 g |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 230V |
| Operating voltage type | AC |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 230 VAC |
| Rated operational current | 35 mA |
| Rated inrush current | 450 mA |
| Protection class | Protection class 2 |
| Pollution degree | 3 |
| Overvoltage category | II |
| Isolation voltage | Ui = 250V; Uimp = 2.500V |

| ACUSTICAL DATA | |
|---|---|
| Volume (max) at 1m distance | 85,0 dB (A) |
| Acoustic signal image | Continuous tone<br>Pulse tone |
| Audio frequency | 2500 Hz |
| Acoustic service life | 5,000 h minimum |

| APPROVAL DATA | |
|---|---|
| Conforms with CE | Yes |
| WEEE | Yes |
| Conforms with RED directive | No |
| Conform with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12 |
| Conforms with FCC | No |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

KombiSIGN 50 / Buzzer Devices 849

# Buzzer element contin/pulse 230VAC BK

| | |
|---|---|
| Conforms with IC | No |
| EAC certificate available | Yes |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with GL | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |

**DRAWING**




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.